

In the Claims:

**Please amend claims 1 and 2 as follows:**

1. (Currently Amended) A method for mapping data to a multi-spline model, the data being expressed in spatial coordinates, the method comprising ~~the~~ steps of:

- (a) constructing a single multi-spline tree from a plurality of splines;
- (b) converting a spatial coordinate of the data to a time-based coordinate; and
- (c) mapping each point of the data to a point on said multi-spline model at least partially according to said time-based coordinate.

2. (Currently Amended) The method of claim 1, further comprising ~~the~~ steps of:

- (d) determining a location in the data by navigating through said multi-spline model; and
- (e) transmitting at least a portion of the data according to said location.

**[Please add new claims 3-14 as follows:]**

3. (New) The method of claim 1, wherein said multi-spline tree features a plurality of nodes, and each of said nodes comprises a spline.

4. (New) The method of claim 3, wherein a child spline of each spline maintains a path of said spline with continuity.

5. (New) The method of claim 1, wherein said constructing said multi-spline tree further comprises:

- determining a root node;
- determining a distance between a new spline and existing splines in said tree;
- locating said new spline on a branch of said tree, in an appropriate location with regard to a time parameter of said new spline; and

expanding said branch according to a derivate of said branch and said new spline.

6. (New) The method of claim 4, wherein said determining said root node, determining said distance, locating said new spline and expanding said branch are repeated until a goal is reached.

7. (New) The method of claim 5, wherein said goal comprises attaching said new splines to said tree.

8. (New) The method of claim 1, wherein said mapping further comprises:

assigning each said point of said data to a branch on said multi-spline tree; and determining correct parameters for each said point of said data.

9. (New) The method of claim 8, wherein said determining correct parameters comprises determining the time on said spline at said point, the angle around said spline at said point and the radius between said point and said spline at said time.

10. (New) The method of claim 9, wherein said determining further comprises selecting a solution wherein said radius is minimal.

11. (New) The method of claim 7 further comprising applying a Path Binding Transform.

12. (New) The method of claim 1, wherein said data comprises X-ray simulation data.

13. (New) The method of claim 1, wherein said data comprises three dimensional data, wherein said three dimensional data is represented in XYZ coordinates and can be analyzed according to time.

B3

14. (New) The method of claim 13, wherein said three dimensional data comprises at least video data.

---